

1000 SERIES LOW RESISTANCE STANDARDS

- *HIGH STABILITY*
- *LOW TEMPERATURE COEFFICIENTS*
- *1 $\mu\Omega$ TO 1 Ω RANGE*
- *INCLUDES ACCREDITED CALIBRATION*

Ohm-Labs' 1000-series low resistance standards are highly stable resistors designed for laboratory or on-site calibration use.

The low temperature and power coefficients allow them to be used in a variety of environments without loss of accuracy. They are not significantly affected by changes in barometric pressure or relative humidity, and are will withstand moderate vibration and shock. They feature low reactance, allowing their use as both dc or ac standards.

All models are housed in a rugged, die-cast aluminum case.

Potential connections are made via gold plated five-way binding posts which accept bare wire, spade lugs or banana jacks.

Current connections are by binding posts or threaded posts, depending on current range.

All models are supplied with ISO17025 Accredited calibration, including data, traceability and uncertainty.

All models are available with an optional temperature sensor bonded to the resistance element. Decade values are standard; other values are available.



MODEL 1004

Model	Resistance	Current	TCR	Accuracy
1000	1 Ω	1 A	<1	<5 ppm
1001	100 m Ω	3	<1	<10
1002	10 m Ω	10	<2	<20
1003	1 m Ω	30	<5	<50
1004	100 $\mu\Omega$	100	<20	<100
1005	10 $\mu\Omega$	100	<50	<300
1006	1 $\mu\Omega$	100	<50	<300

For special values, use the below examples:
 1 =1000 series; X = Resistance; Y = Multiplier

Model	Current	Resistance	Accuracy
1 05 0	2 A	0.5 Ohm	from next lower R
1 25 4	60 A	0.25 mOhm	

All Resistance Standards carry a five year warranty.

Physical:

23 x 12.5 x 12.5 cm / 9 x 5 x 5 in; 2.5 kg / 5 lbs



ISO17025 accredited calibration included.

